


**Digiviewer  
Model 220X**
**Key Features and Advantages:**

The Digiviewer has several distinct advantages over traditional optical binoculars. Those advantages include automatic focusing, one touch zoom control, lighter weight and ease of use. In addition, the viewing end has one large cushioned opening that encompasses both eyes, allowing for a more comfortable viewing experience.

**Product Specifications:**

Model Number	Digiviewer db-220X
Type	Digital Binoculars
Optical Zoom	22 X
Digital Zoom	10 X (22x-220x)
Weight	28.6 oz. (810 g) (w/out battery)
TFT-LCD size	2.45" (diagonal)
Display Resolution	480 x 234
Image Sensor	1/4" interline CCD (sony)
Viewing Angle	47.9° wide, 2.3° tele
Gain Control	Automatic
Shutter	1/60 – 1/100,000 second
White Balance	AWB, 3100K, 5100k, Manual R/B
Min. Illumination	3 lux (F/#1.6)
Video Output	1.0 Vp-p
Battery Power	7.4V 2400mAh
External Power	Input: 120VAC 60Hz 15W
External Power	Output: 7.5VDC 1.0A
Operating Temp.	-5° C ~ +50° C

**For Information Contact:**
**Sightwave Optics**

David Bellefeuille – President  
 Address: 4139 Creekside Pass  
 Zionsville, In 46077  
 Telephone: 317-513-8322  
 Fax: 317-733-8478  
 Email: [info@sightwaveoptics.com](mailto:info@sightwaveoptics.com)  
[www.sightwaveoptics.com](http://www.sightwaveoptics.com)


**Digiviewer  
Model 220X**
**Key Features and Advantages:**

The Digiviewer has several distinct advantages over traditional optical binoculars. Those advantages include automatic focusing, one touch zoom control, lighter weight and ease of use. In addition, the viewing end has one large cushioned opening that encompasses both eyes, allowing for a more comfortable viewing experience.

**Product Specifications:**

Model Number	Digiviewer db-220X
Type	Digital Binoculars
Optical Zoom	22 X
Digital Zoom	10 X (22x-220x)
Weight	28.6 oz. (810 g) (w/out battery)
TFT-LCD size	2.45" (diagonal)
Display Resolution	480 x 234
Image Sensor	1/4" interline CCD (sony)
Viewing Angle	47.9° wide, 2.3° tele
Gain Control	Automatic
Shutter	1/60 – 1/100,000 second
White Balance	AWB, 3100K, 5100k, Manual R/B
Min. Illumination	3 lux (F/#1.6)
Video Output	1.0 Vp-p
Battery Power	7.4V 2400mAh
External Power	Input: 120VAC 60Hz 15W
External Power	Output: 7.5VDC 1.0A
Operating Temp.	-5° C ~ +50° C

**For Information Contact:**
**Sightwave Optics**

David Bellefeuille – President  
 Address: 4139 Creekside Pass  
 Zionsville, In 46077  
 Telephone: 317-513-8322  
 Fax: 317-733-8478  
 Email: [info@sightwaveoptics.com](mailto:info@sightwaveoptics.com)  
[www.sightwaveoptics.com](http://www.sightwaveoptics.com)


**Digiviewer  
Model 220X**
**Key Features and Advantages:**

The Digiviewer has several distinct advantages over traditional optical binoculars. Those advantages include automatic focusing, one touch zoom control, lighter weight and ease of use. In addition, the viewing end has one large cushioned opening that encompasses both eyes, allowing for a more comfortable viewing experience.

**Product Specifications:**

Model Number	Digiviewer db-220X
Type	Digital Binoculars
Optical Zoom	22 X
Digital Zoom	10 X (22x-220x)
Weight	28.6 oz. (810 g) (w/out battery)
TFT-LCD size	2.45" (diagonal)
Display Resolution	480 x 234
Image Sensor	1/4" interline CCD (sony)
Viewing Angle	47.9° wide, 2.3° tele
Gain Control	Automatic
Shutter	1/60 – 1/100,000 second
White Balance	AWB, 3100K, 5100k, Manual R/B
Min. Illumination	3 lux (F/#1.6)
Video Output	1.0 Vp-p
Battery Power	7.4V 2400mAh
External Power	Input: 120VAC 60Hz 15W
External Power	Output: 7.5VDC 1.0A
Operating Temp.	-5° C ~ +50° C

**For Information Contact:**
**Sightwave Optics**

David Bellefeuille – President  
 Address: 4139 Creekside Pass  
 Zionsville, In 46077  
 Telephone: 317-513-8322  
 Fax: 317-733-8478  
 Email: [info@sightwaveoptics.com](mailto:info@sightwaveoptics.com)  
[www.sightwaveoptics.com](http://www.sightwaveoptics.com)